

*Spring Security UI Plugin
Reference Documentation*



GRAILS

Spring Security UI Plugin - Reference Documentation

Burt Beckwith

Version 3.0.0.M2

Table of Contents

1. Introduction to the Spring Security UI Plugin.....	1
1.1. Release History	1
2. User Management	3
2.1. User search	3
2.2. User edit	4
2.3. User creation	6
3. Role Management	7
3.1. Role search.....	7
3.2. Role edit	7
3.3. Role creation	8
4. Requestmap Management	9
4.1. Requestmap search	9
4.2. Requestmap edit	9
4.3. Requestmap creation	10
5. User Registration	11
5.1. Registration	11
5.2. Configuration	12
5.3. Mail configuration	13
5.4. Notes	13
5.5. RegistrationCode search.....	14
5.6. RegistrationCode edit	15
6. Forgot Password.....	16
6.1. Forgot Password	16
6.2. Configuration	18
6.3. Mail configuration	18
6.4. Notes	18
7. ACL Management.....	20
7.1. AclClass Management	20
7.2. AclSid Management.....	21
7.3. AclObjectIdentity Management	23
7.4. AclEntry Management	25
8. Persistent Cookie Management	28
8.1. Persistent logins search	28
8.2. Persistent logins edit	29
8.3. Persistent logins creation.....	29
9. Security Configuration UI	30
9.1. Security Configuration	30
9.2. Mappings	30

9.3. Current Authentication.....	31
9.4. User Cache	31
9.5. Filter Chains	32
9.6. Logout Handlers	33
9.7. Voters	33
9.8. Authentication Providers	33
9.9. Secure Channel Definition	34
10. Customization.....	35
10.1. s2ui-override script	35
10.2. I18N	37
10.3. application.groovy attributes	37
10.4. CSS and JavaScript.....	38
10.5. Password Hashing	40
10.6. Password Verification.....	41
11. Scripts.....	43
11.1. s2ui-override.....	43

Chapter 1. Introduction to the Spring Security UI Plugin

The Spring Security UI plugin provides CRUD screens and other user management workflows. Non-default functionality is available only if the feature is available; this includes the ACL controllers and views which are enabled if the [ACL plugin](#) is installed, Requestmaps support which is available if `grails.plugin.springsecurity.securityConfigType` is set to `"Requestmap"` or `SecurityConfigType.Requestmap` in `application.groovy`, and persistent cookies support which is enabled if it has been configured with the `s2-create-persistent-token` script.

To support both Grails 3.0.x and 3.1.x applications, the plugin depends on version 5.0.x of the hibernate4 plugin and the grails-data-mapping libraries. Because of the way that dependency resolution works across Grails versions, you must add explicit dependencies for the hibernate4 plugin and the GORM libraries to ensure that everything is in sync. As of this writing the current release version of the hibernate4 plugin is '5.0.4' and '5.0.4.RELEASE' for the grails-data-mapping libraries. In addition to adding a dependency for this plugin, add these to the `dependencies` block of your `build.gradle`:



```
compile 'org.grails.plugins:hibernate4:5.0.4'

compile 'org.grails:grails-datastore-core:5.0.4.RELEASE'
compile 'org.grails:grails-datastore-gorm-support:5.0.4.RELEASE'
compile 'org.grails:grails-datastore-gorm:5.0.4.RELEASE'
compile 'org.grails:grails-datastore-simple:5.0.4.RELEASE'
compile 'org.grails:grails-datastore-gorm-hibernate4:5.0.4.RELEASE'
compile 'org.grails:grails-datastore-gorm-hibernate-core:5.0.4.RELEASE'
```

If you use MongoDB or another NoSQL datastore other than Hibernate, retain the supporting dependencies but update the datastore-specific dependencies as necessary.

Also be sure to update the versions when new releases are available.

1.1. Release History

- April 15, 2016
 - 3.0.0.M2 release
- December 21, 2015
 - 3.0.0.M1 release
- December 21, 2015
 - 1.0-RC3 release

- May 20, 2014
 - 1.0-RC2 release
- November 11, 2013
 - 1.0-RC1 release
 - [JIRA Issues](#)
- February 12, 2012
 - 0.2 release
 - [JIRA Issues](#)
- September 14, 2010
 - 0.1.2 release
 - [JIRA Issues](#)
- July 27, 2010
 - 0.1.1 release
- July 26, 2010
 - initial 0.1 release

Chapter 2. User Management

2.1. User search

The default action for the User controller is search. By default only the standard fields (`username`, `enabled`, `accountExpired`, `accountLocked`, and `passwordExpired`) are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

You can search by any combination of fields, and the `username` field has an Ajax autocomplete to assist in finding instances. In this screenshot you can see that an `email` field has been added to the domain class and UI. Leave all fields empty and all checkboxes set at "Either" to return all instances.

The screenshot shows the Spring Security Management Console interface. At the top, there is a navigation bar with links for 'Users', 'Roles', 'Registration Code', and 'Security Info'. The main title is 'Spring Security Management Console' and it indicates the user is logged in as 'admin' with a 'Logout' link. The central part of the interface is a 'User Search' form. It contains two input fields for 'Username' and 'Email'. Below these are four rows of checkboxes for filtering search results: 'Enabled', 'Account Expired', 'Account Locked', and 'Password Expired'. Each row has three columns: 'True', 'False', and 'Either'. The 'Either' column for all four rows has a checked checkbox. A 'Search' button is located at the bottom left of the form area.

This example shows a search for usernames containing 'adm' (the search is case-insensitive and the search string can appear anywhere in the username). Results are shown paginated in groups of 10. All of the column headers are clickable and will sort the results by that field.

User Search

Username:

Email:

	True	False	Either
Enabled:	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Account Expired:	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Account Locked:	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Password Expired:	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Username	Email	Enabled	Account Expired	Account Locked	Password Expired
farzadmiraiei	farzadmiraiei@foo.com	True	False	False	False
cadmus	cadmus@foo.com	True	False	False	False
chenreadme	chenreadme@foo.com	True	False	False	False
admatha	admatha@foo.com	True	False	False	False
sajjadmohebi	sajjadmohebi@foo.com	True	False	False	False
cadmo	cadmo@foo.com	True	False	False	False
padmawar	padmawar@foo.com	True	False	False	False
padma	padma@foo.com	True	False	False	False
ysunadmin	ysunadmin@foo.com	True	False	False	False
farzadmokh	farzadmokh@foo.com	True	False	False	False

1 [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

Showing 1 through 10 out of 100.

2.2. User edit

After clicking through to the 'admin' User you get to the edit page (there are no view pages):

Edit User

User Details Roles

Username

Email

Password

Enabled

Account Expired

Account Locked

Password Expired

You can update any of the attributes or delete the User. You can see that there's a "Login as user" button here - that is only shown if you're authenticated with a User who is granted `ROLE_SWITCH_USER` (this role name can be configured in `application.groovy`):

This allows you to temporarily assume the identity of another User (see [the Spring Security Core plugin documentation](#) for more information about switch-user). The "Logged in as ..." information in the top right of the screen will change to show that you're running as another User and provide a link to switch back. The role name `ROLE_SWITCH_USER` is the default but you can change the value with the `grails.plugin.springsecurity.ui.switchUserRoleName` setting in `application.groovy`.

If you click the Roles tab you can see the roles granted to this User and can click through to its edit page:

Edit User

User Details Roles

`ROLE_ADMIN`

`ROLE_SWITCH_USER`

`ROLE_USER`

2.3. User creation

You can create new Users by going to `/user/create` or by clicking the `Create` action in the `Users` menu.

Users Roles Registration Code Security Info

Spring Security Management Console Logged in as admin (Logout)

Create User

User Details Roles

Username

Email

Password

Enabled

Account Expired

Account Locked

Password Expired

Create

Chapter 3. Role Management

3.1. Role search

The default action for the Role controller is search. By default only the `authority` field is available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

The `authority` field has an Ajax autocomplete to assist in finding instances. Leave the field empty to return all instances.




The screenshot shows the Spring Security Management Console interface. At the top, there is a navigation bar with links for 'Users', 'Roles', 'Registration Code', and 'Security Info'. The main title is 'Spring Security Management Console' and it indicates the user is logged in as 'admin' with a 'Logout' link. The central panel is titled 'Role Search' and contains a text input field labeled 'Authority:' and a 'Search' button.

Search is case-insensitive and the search string can appear anywhere in the name (and you can omit the `ROLE_` prefix). Results are shown paginated in groups of 10 but if there's only one result you'll be forwarded to the edit page for that Role. The `authority` column header is clickable and will sort the results by that field.

3.2. Role edit

After clicking through to a Role you get to the edit page (there are no view pages):



The screenshot shows the Spring Security Management Console interface for editing a role. The navigation bar is the same as in the previous screenshot. The main title is 'Spring Security Management Console' and it indicates the user is logged in as 'admin' with a 'Logout' link. The central panel is titled 'Edit Role' and has two tabs: 'Role Details' (selected) and 'Users'. The 'Role Details' tab contains a text input field labeled 'Authority' with the value 'ROLE_ADMIN'. Below the input field are two buttons: 'Update' and 'Delete'.

You can update any of the attributes or delete the Role. Any user that had been granted the Role will lose the grant but otherwise be unaffected.

If you click the Users tab you can see which users have a grant for this Role and can click through to

their edit page:

The screenshot shows the 'Edit Role' page in the Spring Security Management Console. At the top, there is a navigation bar with links for 'Users', 'Roles', 'Registration Code', and 'Security Info'. The page title is 'Spring Security Management Console' and the user is logged in as 'admin' with a 'Logout' link. The main content area has two tabs: 'Role Details' (selected) and 'Users'. Below the tabs is a large text input field containing the role name 'admin'. At the bottom of the form, there are two buttons: 'Update' and 'Delete'.

3.3. Role creation

You can create new Roles by going to </role/create> or by clicking the **Create** action in the **Roles** menu.

The screenshot shows the 'Create Role' page in the Spring Security Management Console. At the top, there is a navigation bar with links for 'Users', 'Roles', 'Registration Code', and 'Security Info'. The page title is 'Spring Security Management Console' and the user is logged in as 'admin' with a 'Logout' link. The main content area has a title bar 'Create Role'. Below the title bar is a form with a label 'Authority' and an empty text input field. At the bottom of the form, there is a 'Create' button.


Chapter 4. Requestmap Management

The default approach to securing URLs is with annotations, so the Requestmaps menu is only shown if `grails.plugin.springsecurity.securityConfigType` has the value "Requestmap" or `SecurityConfigType.Requestmap` in `application.groovy`.

4.1. Requestmap search


The default action for the Requestmap controller is search. By default only the standard fields (`url` and `configAttribute`) are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

You can search by any combination of fields, and the `url` and `configAttribute` fields have an Ajax autocomplete to assist in finding instances. Leave both fields empty to return all instances.



The screenshot shows the Spring Security Management Console interface. At the top, there is a navigation bar with links for Users, Roles, Requestmaps, Registration Code, and Security Info. The user is logged in as admin, with a Logout link. The main heading is "Spring Security Management Console". Below this is a "Requestmap Search" form with two input fields: "URL:" and "Config Attribute:". A "Search" button is located below the fields.

Searching is case-insensitive and the search string can appear anywhere in the field. Results are shown paginated in groups of 10 and you can click on either header to sort by that field:



The screenshot shows the Spring Security Management Console interface with search results. The navigation bar and user information are the same as in the previous screenshot. The "Requestmap Search" form is still visible. Below the form, there is a table with two columns: "URL" and "Config Attribute". The table contains two rows of results.

URL	Config Attribute
/j_spring_security_switch_user	ROLE_SWITCH_USER,IS_AUTHENTICATED_FULLY
/secure/**	ROLE_ADMIN

Showing 1 through 2 out of 2.

4.2. Requestmap edit

After clicking through to a Requestmap you get to the edit page (there are no view pages):

Edit Requestmap

URL

Config Attribute

You can update any of the attributes or delete the Requestmap. Editing or deleting a Requestmap resets the cache of loaded instances, so your changes will take effect immediately.

4.3. Requestmap creation

You can create new Requestmaps by going to </requestmap/create> or by clicking the **Create** action in the **Requestmaps** menu.

Create Requestmap

URL


Config Attribute

Creating a Requestmap resets the cache of loaded instances, so your changes will take effect immediately.

Chapter 5. User Registration

Most of the plugin's controllers are intended to be part of a backend admin application, but the Registration and Forgot Password workflows are expected to be user-facing. So they're not available in the admin menu like the User, Role, and other backend functionality - you'll need to expose them to your users.


One way to do this is to replace the default `login.gsp` that's provided by the Spring Security Core plugin with this plugin's version. You can do this by running `grails s2ui-override auth - s2ui-override` script - see the [Customization](#) section for details. If you do this your users will have links to both workflows from the login screen:



The image shows a 'Member sign in' form. It has a title 'Member sign in' at the top. Below the title are two input fields: 'Username:' and 'Password:'. Below the password field is a checkbox labeled 'Remember me' and a link 'Forgot password?'. At the bottom of the form are two buttons: 'Register as new User' and 'Log in'.


5.1. Registration

Navigate to `/register/`:




The image shows a 'Create Account' form. It has a title 'Create Account' at the top. Below the title are four input fields: 'Username', 'E-mail', 'Password', and 'Password (again)'. Below the password fields is a button labeled 'Create your account'.

After filling out valid values an email will be sent and you'll see a success screen:




Click on the link in the email:



and you'll finalize the process, which involves enabling the locked user and pre-authenticating, then redirecting to the configured destination:



 Your registration is complete

Logged in as testuser (**Logout**)

5.2. Configuration

The post-registration destination url is configurable in `grails-app/conf/application.groovy` using the `postRegisterUrl` attribute:


```
grails.plugin.springsecurity.ui.register.postRegisterUrl = '/welcome'
```

If you don't specify a value then the `grails.plugin.springsecurity.successHandler.defaultTargetUrl` value will be used, which is `'/'` by default.

You can customize the subject, body, and from address of the registration email by overriding the default values in `grails-app/conf/application.groovy`, for example:

```
grails.plugin.springsecurity.ui.register.emailBody = '...'  
grails.plugin.springsecurity.ui.register.emailFrom = '...'  
grails.plugin.springsecurity.ui.register.emailSubject = '...'
```

The `emailBody` property should be a GString and will have the User domain class instance in scope in the `user` variable, and the generated url to click to finalize the signup in the `url` variable.

In addition, each new user will be granted `ROLE_USER` after finalizing the registration. If you want to change the default role, add more, or grant no roles at all (for example if you want an admin to approve new users and explicitly enable new users) then you can customize that with the `defaultRoleNames` attribute (which is a List of Strings):

```
grails.plugin.springsecurity.ui.register.defaultRoleNames = [] // no roles
```

or

```
grails.plugin.springsecurity.ui.register.defaultRoleNames = ['ROLE_CUSTOMER']
```

5.3. Mail configuration

By default the plugin uses the `Mail` plugin to send emails, but only if it installed. This is configurable by registering your own `MailStrategy` implementation - see [the section on configuration|guide:customization] for more information. The plugin assumes that the Mail plugin and an SMTP server are already configured.

5.4. Notes

You should consider the registration code as starter code - every signup workflow will be different, and this should help you get going but is unlikely to be sufficient. You may wish to collect more information than just username and email - first and last name for example. Run `grails s2ui-override register` to copy the registration controller and GSPs into your application to be customized.

If there are unexpected validation errors during registration (which can happen when there is a disconnect between the domain classes and the code in `RegisterController` they will be logged at the `warn` or `error` level, so enable logging to ensure that you see the messages, e.g.

```
...
logger 'grails.plugin.springsecurity.ui.SpringSecurityUiService', WARN
...
```



`RegisterController` and its GSPs assume that your User domain class has an `email` field. Be sure to either rework the workflow (using the `s2ui-override` script) if you don't need an email confirmation step or add an email field.

5.5. RegistrationCode search

The plugin uses its `grails.plugin.springsecurity.ui.RegistrationCode` domain class to store a token associated with the new users' username for use when finishing the registration process after the user clicks the link in the generated email (and also as part of the forgot-password workflow). The plugin includes a controller and GSPs to manage these instances.

The default action for the `RegistrationCode` controller is `search`. By default only the standard fields (`username` and `token`) are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

You can search by any combination of fields, and both fields have an Ajax autocomplete to assist in finding instances. Leave both fields empty to return all instances.

The screenshot shows the Spring Security Management Console interface. At the top, there is a navigation bar with links for Users, Roles, Requestmaps, Registration Code, ACL, and Security Info. The user is logged in as admin, with a Logout link. The main content area is titled "Spring Security Management Console" and contains a "Registration Code Search" form. The form has two input fields: "Username:" and "Token:". Below the fields is a "Search" button.

Searching is case-insensitive and the search string can appear anywhere in the field. Results are shown paginated in groups of 10 and you can click on any header to sort by that field:

Registration Code Search

Username:

Token:

Token	Username	Date Created
e81b1e53648a47e6aef31a937154c7cb	registration_test_1	2015-12-19
4a7f88afec3746f7aab2f5d0d8df6d8e	registration_test_1	2015-12-19
c7ac5f23be70495f93e4450a78a27cb4	registration_test_1	2015-12-19
a50e061e0e2f424fb7fbc2ff3dae597d	registration_test_1	2015-12-19
d6938ad63c414a69a0da30a8c0619a60	registration_test_2	2015-12-19
4a589c642ea143abb2ecaea57fa0a0cc	registration_test_2	2015-12-19
0a154624f36d42e4aa68991a9477bd04	registration_test_2	2015-12-19
3842a6ae102a431c8e48177c16720713	registration_test_3	2015-12-19
84cefa66465a460c82f46120d9098686	registration_test_3	2015-12-19
fd1e40a7b31f4e8282a2a789135ed21d	registration_test_3	2015-12-19

1

Showing 1 through 10 out of 14.

5.6. RegistrationCode edit

After clicking through to a RegistrationCode you get to the edit page (there are no view pages):

Edit RegistrationCode

Username

Token

Date Created 2015-12-19


You can update the `username` or `token` attribute or delete the RegistrationCode.

Since instances are created during the "User Registration" and "Forgot Password" workflows, there is no functionality in this plugin to create new instances.

Chapter 6. Forgot Password

Like the Registration workflow, the Forgot Password workflow is expected to be user-facing. So it's not available in the admin menu like the User, Role, and other backend functionality - you'll need to expose them to your users.


One way to do this is to replace the default `login.gsp` that's provided by the Spring Security Core plugin with this plugin's version. You can do this by running `grails s2ui-override auth` - see the section on [Customization](#) for more details. If you do this your users will have links to both workflows from the login screen:



The image shows a 'Member sign in' form. It has a title 'Member sign in' at the top. Below the title are two input fields: 'Username:' and 'Password:'. Below the password field is a checkbox labeled 'Remember me' which is checked, followed by a link 'Forgot password?'. At the bottom of the form are two buttons: 'Register as new User' and 'Log in'.


6.1. Forgot Password

Navigate to `/register/forgotPassword:`




The image shows a 'Forgot Password' form. It has a title 'Forgot Password' at the top. Below the title is a message: 'Enter your username and we'll send a link to reset your password to the address we have for your account.' Below the message is an input field labeled 'Username'. Below the input field is a button labeled 'Reset my password'.

After entering a valid username an email will be sent and you'll see a success screen:



Click on the link in the email:



and you'll open the reset password form:

A screenshot of a "Reset Password" form. At the top, there is a grey button with the text "Reset Password". Below the button, the text reads: "Enter your new password". There are two input fields: "Password" and "Password (again)". Below the input fields, there is a grey button with the text "Update my password".

After entering a valid password you'll finalize the process, which involves storing the new

password hashed in the user table and pre-authenticating, then redirecting to the configured destination:



 Your password was successfully changed

Logged in as testuser (Logout)

6.2. Configuration

The post-reset destination url is configurable in `grails-app/conf/application.groovy` using the `postResetUrl` attribute:

```
grails.plugin.springsecurity.ui.forgotPassword.postResetUrl = '/reset'
```

If you don't specify a value then the `defaultTargetUrl` value will be used, which is `'/'` by default.

You can customize the subject, body, and from address of the reset email by overriding the default values in `grails-app/conf/application.groovy`, for example:

```
grails.plugin.springsecurity.ui.forgotPassword.emailBody = '...'  
grails.plugin.springsecurity.ui.forgotPassword.emailFrom = '...'  
grails.plugin.springsecurity.ui.forgotPassword.emailSubject = '...'
```

The `emailBody` property should be a GString and will have the User domain class instance in scope in the `user` variable, and the generated url to click to reset the password in the `url` variable.

6.3. Mail configuration

By default the plugin uses the [Mail](#) plugin to send emails, but only if it installed. This is configurable by registering your own `MailStrategy` implementation - see [the section on configuration|guide:customization] for more information. The plugin assumes that the Mail plugin and an SMTP server are already configured.

6.4. Notes

Like the registration code, consider this workflow as starter code. Run `grails s2ui-override register` to copy the registration controller and GSPs into your application to be customized.



`RegisterController` and its GSPs assume that your User domain class has an `email` field.

Chapter 7. ACL Management


ACL management should be done using the API exposed by `AcLService` and `AcLUtiLService`. Both services have a much more intuitive and convenient high-level approach to managing ACLs, ACEs, etc. The functionality in this plugin is to provide a CRUD interface for fine-grained ACL management.

The ACL menu is only available if the [ACL plugin](#) is installed.


7.1. AcLClass Management

The default action for the `AcLClass` controller is search. By default only the standard fields are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

The `className` field has an Ajax autocomplete to assist in finding instances. Leave the field empty to return all instances.



Searching is case-insensitive and the search string can appear anywhere in the field. Results are shown paginated in groups of 10 and you can click on the `className` column header to sort the results by that field:



7.1.1. AcLClass Edit

After clicking through an `AcLClass` you get to the edit page (there are no view pages):

Edit AclClass

Class Name

[View Associated OIDs](#)

[View Associated ACL Entries](#)

You can update the name, and delete the instance if there aren't any associated `AclObjectIdentity` or `AclEntry` instances - by default there is no support for cascading.

You can also see the associated `AclObjectIdentity` instances (OIDs) or `AclEntry` instances.

7.1.2. AclClass Create

You can create new instances by going to `/aclClass/create` or by clicking the `Create` action in the `Class` menu under `ACL`.

Create AclClass

Class Name

7.2. AclSid Management

The default action for the `AclSid` controller is search. By default only the standard fields are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

The `sid` field has an Ajax autocomplete to assist in finding instances. Leave the field empty and `principal` set to `Either` to return all instances.

AclSid Search

SID:

Principal: True False Either

Results are shown paginated in groups of 10. The column headers are clickable and will sort the results by that field:

AclSid Search

SID:

Principal: True False Either

SID	Principal
user2	True
admin	True
user1	True

Showing 1 through 3 out of 3.

7.2.1. AclSid Edit

After clicking through to a sid you get to the edit page (there are no view pages):

Edit AclSid

SID:

Principal:

[View Associated OIDs](#)

[View Associated ACL Entries](#)


You can update the name and whether it's a Principal sid or a Role sid, and delete the instance if there aren't any associated `AclobjectIdentity` or `AclEntry` instances - by default there is no support

for cascading.

You can also see the associated `AcObjectIdentity` instances (OIDs) or `AcEntry` instances.

7.2.2. AclSid Create

You can create new instances by going to `/aclSid/create` or by clicking the `Create` action in the `SID` menu under `ACL`.




The screenshot shows the 'Create AclSid' form in the Spring Security Management Console. The page header includes navigation links for 'Users', 'Roles', 'Registration Code', 'ACL', and 'Security Info', and indicates the user is logged in as 'admin' with a 'Logout' link. The form itself has a title bar 'Create AclSid' and contains a text input field for 'SID', a checkbox for 'Principal', and a 'Create' button.

7.3. AcObjectIdentity Management

The default action for the `AcObjectIdentity` controller is search. By default only the standard fields are available but this is customizable with the `s2ui-override` script - see the `Customization` section for details.

Leave all fields at their default values to return all instances.



The screenshot shows the 'AcObjectIdentity Search' form in the Spring Security Management Console. The page header is identical to the previous screenshot. The form has a title bar 'AcObjectIdentity Search' and includes several search criteria: 'AcClass' (dropdown menu set to 'All'), 'Object ID' (text input), 'Owner' (dropdown menu set to 'All'), 'Parent' (text input), and 'Entries Inheriting' (checkboxes for 'True', 'False', and 'Either', with 'Either' selected). A 'Search' button is located at the bottom left of the form.

Results are shown paginated in groups of 10 and you can click on any header to sort by that field:

AclObjectIdentity Search

AclClass:

 Object ID:

 Owner:

 Parent:

Entries Inheriting: True False Either

ID	AclClass	Object ID	Entries Inheriting	Owner	Parent
3	com.burtbeckwith.testapp.domain.Report	3	True	admin	
6	com.burtbeckwith.testapp.domain.Report	6	True	admin	
1	com.burtbeckwith.testapp.domain.Report	1	True	user1	
4	com.burtbeckwith.testapp.domain.Report	4	True	admin	
10	com.burtbeckwith.testapp.domain.Report	10	True	admin	
8	com.burtbeckwith.testapp.domain.Report	8	True	admin	
7	com.burtbeckwith.testapp.domain.Report	7	True	admin	
5	com.burtbeckwith.testapp.domain.Report	5	True	admin	
9	com.burtbeckwith.testapp.domain.Report	9	True	admin	
2	com.burtbeckwith.testapp.domain.Report	2	True	user1	

1

Showing 1 through 10 out of 100.

7.3.1. AclObjectIdentity Edit

After clicking through to an AclObjectIdentity you get to the edit page (there are no view pages):

Edit AclObjectIdentity

AclClass

 Object ID

 Owner

 Parent

Entries Inheriting

[View Associated ACL Entries](#)

You can update any of the attributes, and can delete the instance if there aren't any associated **AcLEntry** instances - by default there is no support for cascading.

You can also see the associated **AcLEntry** instances.

7.3.2. AclObjectIdentity Create

You can create new instances by going to </aclObjectIdentity/create> or by clicking the **Create** action in the **OID** menu under **ACL**.

The screenshot shows the 'Create AclObjectIdentity' form in the Spring Security Management Console. The page header includes navigation links for 'Users', 'Roles', 'Registration Code', 'ACL', and 'Security Info', and indicates the user is logged in as 'admin' with a 'Logout' link. The form contains the following fields:

- AclClass**: A dropdown menu.
- Object ID**: A text input field.
- Owner**: A dropdown menu.
- Parent**: A text input field.
- Entries Inheriting**: A checkbox.
- Create**: A button to submit the form.

7.4. AclEntry Management

The default action for the AclEntry controller is search. By default only the standard fields are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

Leave all fields at their default values to return all instances.

The screenshot shows the 'AclEntry Search' form in the Spring Security Management Console. The page header is identical to the previous screenshot. The form contains the following fields:

- AclObjectIdentity:** A text input field.
- Ace Order:** A text input field.
- SID:** A dropdown menu with 'All' selected.
- Mask:** A text input field.
- Granting:** A row of three checkboxes labeled 'True', 'False', and 'Either'. The 'Either' checkbox is checked.
- Audit Success:** A row of three checkboxes labeled 'True', 'False', and 'Either'. The 'Either' checkbox is checked.
- Audit Failure:** A row of three checkboxes labeled 'True', 'False', and 'Either'. The 'Either' checkbox is checked.
- Search**: A button to submit the search.

Results are shown paginated in groups of 10 and you can click on any header to sort by that field:

AclEntry Search

AclObjectIdentity:

Ace Order:

SID:

Mask:

Granting: True False Either

Audit Success: True False Either

Audit Failure: True False Either

ID	AclObjectIdentity	Ace Order	SID	Mask	Granting	Audit Success	Audit Failure
99	5	2	user2	BasePermission[.....W.=2]	True	False	False
94	4	0	user1	BasePermission[.....R=1]	True	False	False
95	4	1	user2	BasePermission[.....R=1]	True	False	False
100	5	3	admin	BasePermission[.....A....=16]	True	False	False
96	4	2	admin	BasePermission[.....A....=16]	True	False	False
93	3	2	admin	BasePermission[.....A....=16]	True	False	False
91	3	0	user1	BasePermission[.....R=1]	True	False	False
92	3	1	user2	BasePermission[.....R=1]	True	False	False
97	5	0	user1	BasePermission[.....R=1]	True	False	False
98	5	1	user2	BasePermission[.....R=1]	True	False	False

1 ..

Showing 1 through 10 out of 175.

7.4.1. AclEntry Edit

After clicking through to an AclEntry you get to the edit page (there are no view pages):

Edit AclEntry

AclObjectIdentity:

Ace Order:

SID:

Mask:

Granting:

Audit Success:

Audit Failure:

You can update any of the attributes or delete the AclEntry.

7.4.2. AclEntry Create

You can create new instances by going to </aclEntry/create> or by clicking the **Create** action in the

Entry menu under ACL.

Create AclEntry

AclObjectIdentity

Ace Order

SID

Mask

Granting

Audit Success

Audit Failure

Chapter 8. Persistent Cookie Management


Persistent cookies aren't enabled by default - you must enable them by running the `s2-create-persistent-token` script. See [the Spring Security Core plugin documentation](#) for details about this feature.

The Persistent Logins menu is only shown if this feature is enabled.


8.1. Persistent logins search

The default action for the PersistentLogin controller is search. By default only the standard fields (`username`, `token`, and `series`) are available but this is customizable with the `s2ui-override` script - see the [Customization](#) section for details.

You can search by any combination of fields, and all fields have an Ajax autocomplete to assist in finding instances. Leave all fields empty to return all instances.




Searching is case-insensitive and the search string can appear anywhere in the field. Results are shown paginated in groups of 10 and you can click on any header to sort by that field:



8.2. Persistent logins edit

After clicking through to an instance you get to the edit page (there are no view pages):



The screenshot shows the 'Spring Security Management Console' interface. At the top, there is a navigation bar with links for 'Users', 'Roles', 'Persistent Logins', 'Registration Code', and 'Security Info'. The user is logged in as 'admin' with a '(Logout)' link. The main content area is titled 'Edit PersistentLogin' and contains the following fields:

Series	dWEAHu/0ueJGJBpoRMFiGQ==
Username	admin
Token	<input type="text" value="XQl<CHT5wbuywP3RY/+zN6A=="/>
Last Used	<input type="text" value="2010-07-25 17:21:32 EDT"/>

At the bottom of the form, there are two buttons: 'Update' and 'Delete'.


You can update the **token** or **lastUsed** attribute or delete the instance.

8.3. Persistent logins creation

Since instances are created during authentication by the spring-security-core plugin, there is no functionality in this plugin to create new instances.


Chapter 9. Security Configuration UI

The Security Info menu has links for several pages that contain read-only views of much of the Spring Security configuration:



9.1. Security Configuration

The Security Configuration menu item displays all security-related attributes in `application.groovy`. The names omit the `grails.plugin.springsecurity` prefix:



9.2. Mappings

The Mappings menu item displays the current request mapping mode (Annotation, Requestmap, or Static) and all current mappings:

SecurityConfigType: Annotation

Mappings

Pattern	ConfigAttributes	HTTP Method
/	permitAll	all
/index	permitAll	all
/index.gsp	permitAll	all
/assets/**	permitAll	all
/js/	permitAll	all
/css/	permitAll	all
/images/	permitAll	all
**/favicon.ico	permitAll	all
/register	permitAll	all
/register/**	permitAll	all
/registrationcode	permitAll	all
/registrationcode/**	permitAll	all
/securityinfo	permitAll	all
/securityinfo/**	permitAll	all
/login	permitAll	all
/login.*	permitAll	all
/login/**	permitAll	all
/logout	permitAll	all
/logout.*	permitAll	all
/logout/**	permitAll	all

9.3. Current Authentication

The Current Authentication menu item displays your **Authentication** information, mostly for reference to see what a typical one contains:

Current Authentication

Name	Value
Authorities	[ROLE_RUN_AS, ROLE_USER, ROLE_ADMIN, ROLE_SWITCH_USER]
Details	org.springframework.security.web.authentication.WebAuthenticationDetails@ffed504: RemoteIpAddress: 127.0.0.1; SessionId: 659C5EEAED7F26774E7214E7F0D35D3D
Principal	grails.plugin.springsecurity.userdetails.GrailsUser@586034f: Username: admin; Password: [PROTECTED]; Enabled: true; AccountNonExpired: true; credentialsNonExpired: true; AccountNonLocked: true; Granted Authorities: ROLE_ADMIN,ROLE_RUN_AS,ROLE_SWITCH_USER,ROLE_USER
Name	admin

9.4. User Cache

The User Cache menu item displays information about cached users if the feature is enabled (it is disabled by default).

UserCache class: net.sf.ehcache.Cache

User Cache

Attribute	Value
Size	1
Status	STATUS_ALIVE
Name	userCache
GUID	127.0.1.1-458656cf-0031-4216-8f6d-ee25a6438d98

Statistics

Attribute	Value
Cache Hits	1
In-memory Hits	2
On-disk Hits	0
Cache Misses	3
Object Count	1
Memory Store Object Count	1
Disk Store Object Count	0
Eviction Count	0

1 Cached User(s)

Username	User
admin	grails.plugin.springsecurity.userdetails.GrailsUser@586034f: Username: admin; Password: [PROTECTED]; Enabled: true; AccountNonExpired: true; credentialsNonExpired: true; AccountNonLocked: true; Granted Authorities: ROLE_ADMIN,ROLE_RUN_AS,ROLE_SWITCH_USER,ROLE_USER

9.5. Filter Chains

The Filter Chains menu item displays your configured Filter chains. It is possible to have multiple URL patterns each with its own filter chain, for example when using HTTP Basic Auth for a web service. By default since the 3.0.0 release the spring-security-core `s2-quickstart` script configures empty filter chains for static assets to avoid unnecessary security checks (although of course if you need to secure some or all of your static assets you should reconfigure these).

Filter Chains

URL Pattern	Filters
Ant [pattern='/assets/**']	none
Ant [pattern='/**/js/**']	none
Ant [pattern='/**/css/**']	none
Ant [pattern='/**/images/**']	none
Ant [pattern='/**/favicon.ico']	none
Ant [pattern='/**']	grails.plugin.springsecurity.web.SecurityRequestHolderFilter org.springframework.security.web.access.channel.ChannelProcessingFilter org.springframework.security.web.context.SecurityContextPersistenceFilter grails.plugin.springsecurity.web.authentication.logout.MutableLogoutFilter grails.plugin.springsecurity.web.authentication.GrailsUsernamePasswordAuthenticationFilter org.springframework.security.web.servletapi.SecurityContextHolderAwareRequestFilter grails.plugin.springsecurity.web.filter.GrailsRememberMeAuthenticationFilter grails.plugin.springsecurity.web.filter.GrailsAnonymousAuthenticationFilter org.springframework.security.web.access.ExceptionTranslationFilter org.springframework.security.web.access.intercept.FilterSecurityInterceptor org.springframework.security.web.authentication.switchuser.SwitchUserFilter

9.6. Logout Handlers

The Logout Handlers menu item displays your registered `LogoutHandlers`. Typically there will be just the ones shown here, but you can register your own custom implementations, or a plugin might contribute more:

Users Roles Requestmaps Persistent Logins Registration Code ACL Security Info

Spring Security Management Console Logged in as admin (Logout)

Logout Handlers

Class Name
<code>org.springframework.security.web.authentication.rememberme.PersistentTokenBasedRememberMeServices</code>
<code>org.springframework.security.web.authentication.logout.SecurityContextLogoutHandler</code>

9.7. Voters

The Voters menu item displays your registered `AccessDecisionVoters`. Typically there will be just the ones shown here, but you can register your own custom implementations, or a plugin might contribute more:

Users Roles Requestmaps Persistent Logins Registration Code ACL Security Info

Spring Security Management Console Logged in as admin (Logout)

Voters

Class Name
<code>org.springframework.security.access.vote.AuthenticatedVoter</code>
<code>org.springframework.security.access.vote.RoleHierarchyVoter</code>
<code>grails.plugin.springsecurity.web.access.expression.WebExpressionVoter</code>
<code>grails.plugin.springsecurity.access.vote.ClosureVoter</code>

9.8. Authentication Providers

The Authentication Providers menu item displays your registered `AuthenticationProviders`. Typically there will be just the ones shown here, but you can register your own custom implementations, or a plugin (e.g. LDAP) might contribute more:

Users Roles Requestmaps Persistent Logins Registration Code ACL Security Info

Spring Security Management Console Logged in as admin (Logout)

Authentication Providers

Class Name
<code>org.springframework.security.authentication.dao.DaoAuthenticationProvider</code>
<code>grails.plugin.springsecurity.authentication.GrailsAnonymousAuthenticationProvider</code>
<code>org.springframework.security.authentication.RememberMeAuthenticationProvider</code>

9.9. Secure Channel Definition

The Secure Channel Definition menu item displays your registered channel security mappings.

Users	Roles	Persistent Logins	Registration Code	ACL	Security Info	
Spring Security Management Console						Logged in as admin (Logout)
Secure Channel Definition						
Pattern	ConfigAttributes					
Ant [pattern='/secure/stuff/**']	[REQUIRES_SECURE_CHANNEL]					
Ant [pattern='/insecure/stuff/**']	[REQUIRES_INSECURE_CHANNEL]					
Ant [pattern='/**']	[ANY_CHANNEL]					

Chapter 10. Customization

Most aspects of the plugin are configurable.

10.1. s2ui-override script

The plugin's controllers and GSPs are easily overridden using the `s2ui-override` script. The general syntax for running the script is

```
grails s2ui-override <type> <controller-package>
```

The script will copy an empty controller that extends the corresponding plugin controller into your application so you can override individual actions and methods as needed. It also copies the controller's GSPs. The exceptions are 'auth' and 'layout' which only copy GSPs.

The files copied for each type are summarized here:

- `acclass`
 - `controller/AclClassController.groovy`
 - `views/aclClass/create.gsp`
 - `views/aclClass/edit.gsp`
 - `views/aclClass/search.gsp`
- `aclentry`
 - `controller/AclEntryController.groovy`
 - `views/aclEntry/create.gsp`
 - `views/aclEntry/edit.gsp`
 - `views/aclEntry/search.gsp`
- `aclobjectidentity`
 - `controller/AclObjectIdentityController.groovy`
 - `views/aclObjectIdentity/create.gsp`
 - `views/aclObjectIdentity/edit.gsp`
 - `views/aclObjectIdentity/search.gsp`
- `aclsid`
 - `controller/AclSidController.groovy`
 - `views/aclSid/create.gsp`
 - `views/aclSid/edit.gsp`
 - `views/aclSid/search.gsp`
- `auth`
 - `views/login/auth.gsp`
- `layout`

- `views/layouts/springSecurityUI.gsp`
- `views/includes/_ajaxLogin.gsp`
- `persistentlogin`
 - `controller/PersistentLoginController.groovy`
 - `views/persistentLogin/edit.gsp`
 - `views/persistentLogin/search.gsp`
- `register`
 - `controller/RegisterController.groovy`
 - `views/register/forgotPassword.gsp`
 - `views/register/register.gsp`
 - `views/register/resetPassword.gsp`
- `registrationcode`
 - `controller/RegistrationCodeController.groovy`
 - `views/registrationCode/edit.gsp`
 - `views/registrationCode/search.gsp`
- `requestmap`
 - `controller/RequestmapController.groovy`
 - `views/requestmap/create.gsp`
 - `views/requestmap/edit.gsp`
 - `views/requestmap/search.gsp`
- `role`
 - `controller/RoleController.groovy`
 - `views/role/create.gsp`
 - `views/role/edit.gsp`
 - `views/role/search.gsp`
- `securityinfo`
 - `controller/SecurityInfoController.groovy`
 - `views/securityInfo/config.gsp`
 - `views/securityInfo/currentAuth.gsp`
 - `views/securityInfo/filterChains.gsp`
 - `views/securityInfo/logoutHandlers.gsp`
 - `views/securityInfo/mappings.gsp`
 - `views/securityInfo/providers.gsp`
 - `views/securityInfo/secureChannel.gsp`
 - `views/securityInfo/usercache.gsp`
 - `views/securityInfo/voters.gsp`
- `user`
 - `controller/UserController.groovy`

- `views/user/create.gsp`
- `views/user/edit.gsp`
- `views/user/search.gsp`

10.2. I18N

All of the plugin's displayed strings are localized and stored in the plugin's `grails-app/i18n/messages.spring-security-ui.properties` file. You can override any of these values by putting an override in your application's `grails-app/i18n/messages.properties` file.

10.3. application.groovy attributes

There are a few configuration options specified in `DefaultUiSecurityConfig.groovy` that can be overridden in your application's `grails-app/conf/application.groovy`

10.3.1. Registration attributes

These settings are used in the registration workflow; see the [User Registration](#) section for more details:

- `grails.plugin.springsecurity.ui.register.defaultRoleNames`
- `grails.plugin.springsecurity.ui.register.emailBody`
- `grails.plugin.springsecurity.ui.register.emailFrom`
- `grails.plugin.springsecurity.ui.register.emailSubject`
- `grails.plugin.springsecurity.ui.register.postRegisterUrl`

10.3.2. Forgot Password attributes

These settings are used in the forgot-password workflow; see the [Forgot Password](#) section for more details:

- `grails.plugin.springsecurity.ui.forgotPassword.emailBody`
- `grails.plugin.springsecurity.ui.forgotPassword.emailFrom`
- `grails.plugin.springsecurity.ui.forgotPassword.emailSubject`
- `grails.plugin.springsecurity.ui.forgotPassword.postResetUrl`

10.3.3. GSP layout attributes

The `layout` attribute in the GSPs is configurable. If this is the only change you want to make in some or all of the GSPs then you can avoid copying the GSPs into your application just to make this change.

The default value for the registration workflow GSPs (`forgotPassword.gsp`, `register.gsp`, and `resetPassword.gsp`) is “register” and the default for the rest is “springSecurityUI”. These values can be overridden with the `grails.plugin.springsecurity.ui.gsp.layoutRegister` and

`grails.plugin.springsecurity.ui.gsp.layoutUi` settings.

10.3.4. Miscellaneous attributes

The role name required to be able to run as another user defaults to `ROLE_SWITCH_USER` but you can override this name with the `grails.plugin.springsecurity.ui.switchUserRoleName` setting.

10.4. CSS and JavaScript

The plugin uses the [Asset Pipeline](#) plugin to manage its resources. This makes it very easy to provide your own version of some or all of the static resources since asset-pipeline will always use a file in the application's `assets` directory instead of a plugin's if it exists.

Instead of depending on either the jQuery or jQuery UI plugins, this plugin includes its own copy of `jquery.js`, `jquery-ui.js`, and `jquery-ui.css`. Note that the versions are not hard-coded, but instead they take advantage of the feature in asset-pipeline where you can embed Groovy code in a file to specify the name and path.

The layouts use `grails-app/assets/javascripts/jquery.js`, which contains this:

```
//require jquery/jquery-
${grails.plugin.springsecurity.ui.Constants.JQUERY_VERSION}.js
```

This resolves to `grails-app/assets/javascripts/jquery/jquery-2.1.4.js`, and to use your own version, either use the same approach in a file called `jquery.js` or rename your file to `jquery.js`.

Likewise for jQuery UI, the JavaScript file is `grails-app/assets/javascripts/jquery-ui.js`, which contains this

```
//require jquery-ui/jquery-ui-
${grails.plugin.springsecurity.ui.Constants.JQUERY_UI_VERSION}.js
```

and the CSS file `grails-app/assets/stylesheets/jquery-ui.css`, which contains

```
/*
 *= require smoothness/jquery-ui-
 ${grails.plugin.springsecurity.ui.Constants.JQUERY_UI_VERSION}.css
 */
```

The JavaScript file resolves to `grails-app/assets/javascripts/jquery-ui/jquery-ui-1.10.3.custom.js`, and to use your own version, either use the same approach in a file called `jquery-ui.js` or rename your file to `jquery-ui.js`.

The CSS file resolves to `grails-app/assets/stylesheets/smoothness/jquery-ui-1.10.3.custom.css`, and to use your own version, either use the same approach in a file called `jquery-ui.js` or rename your file to `jquery-ui.js`.

Use your own `jquery-ui.js` and/or `jquery-ui.css` to override the plugin's.

The `springSecurityUI.gsp` layout includes `grails-app/assets/stylesheets/spring-security-ui.css`, which has no style declarations and only includes other CSS files:

```
/*
 *= require reset.css
 *= require jquery-ui.css
 *= require jquery.jdMenu.css
 *= require jquery.jdMenu.slate.css
 *= require jquery.jgrowl.css
 *= require spring-security-ui-common.css
 */
```

and `grails-app/assets/javascripts/spring-security-ui.js` which has no JavaScript code and only includes other JavaScript files:

```
//= require jquery.js
//= require jquery-ui.js
//= require jquery/jquery.jgrowl.js
//= require jquery/jquery.positionBy.js
//= require jquery/jquery.bgiframe.js
//= require jquery/jquery.jdMenu.js
//= require jquery/jquery.form.js
//= require spring-security-ui-ajaxLogin.js
```

The `register.gsp` layout layout includes `grails-app/assets/stylesheets/spring-security-ui-register.css`, which has no style declarations and only includes other CSS files:

```
/*
 *= require reset.css
 *= require jquery-ui.css
 *= require jquery.jgrowl.css
 *= require spring-security-ui-common.css
 */
```

and `grails-app/assets/javascripts/spring-security-ui-register.js` which has no JavaScript code and only includes other JavaScript files:

```
//= require jquery.js
//= require jquery-ui.js
//= require jquery/jquery.jgrowl.js
```

The remaining JavaScript files are

- `grails-app/assets/javascripts/spring-security-ui-ajaxLogin.js`

- `grails-app/assets/javascripts/jquery/jquery.bgiframe.js`
- `grails-app/assets/javascripts/jquery/jquery.dataTables.js`
- `grails-app/assets/javascripts/jquery/jquery.form.js`
- `grails-app/assets/javascripts/jquery/jquery.jdMenu.js`
- `grails-app/assets/javascripts/jquery/jquery.jgrowl.js`
- `grails-app/assets/javascripts/jquery/jquery.positionBy.js`

and the remaining CSS files are

- `grails-app/assets/stylesheets/jquery.dataTables.css`
- `grails-app/assets/stylesheets/jquery.jdMenu.css`
- `grails-app/assets/stylesheets/jquery.jdMenu.slate.css`
- `grails-app/assets/stylesheets/jquery.jgrowl.css`
- `grails-app/assets/stylesheets/reset.css`
- `grails-app/assets/stylesheets/spring-security-ui-auth.css`
- `grails-app/assets/stylesheets/spring-security-ui-common.css`

10.5. Password Hashing

In recent versions of the Spring Security Core plugin, the “User” domain class is generated by the `s2-quickstart` script with code to automatically hash the password. This makes the code simpler (for example in controllers where you create users or update user passwords) but older generated classes don’t have this generated code. This presents a problem for plugins like this one since it’s not possible to reliably determine if the domain class hashes the password or if you use the older approach of explicitly calling `springSecurityService.encodePassword()`.

The unfortunate consequence of mixing a newer domain class that does password hashing with controllers that call `springSecurityService.encodePassword()` is the the passwords get double-hashed, and users aren’t able to login. So to get around this there’s a configuration option you can set to tell this plugin’s controllers whether to hash or not: `grails.plugin.springsecurity.ui.encodePassword`.

This option defaults to `false`, so if you have an older domain class that doesn’t handle hashing just enable this plugin’s hashing:

```
grails.plugin.springsecurity.ui.encodePassword = true
```

h4. Strategy classes

The plugin’s `SpringSecurityUiService` implements several “strategy” interfaces to make it possible to override its functionality in a more fine-grained way.

These are defined by interfaces in the `grails.plugin.springsecurity.ui.strategy` package:

- `AcLStrategy`
- `ErrorsStrategy`
- `MailStrategy`
- `PersistentLoginStrategy`
- `PropertiesStrategy`
- `QueryStrategy`
- `RegistrationCodeStrategy`
- `RequestmapStrategy`
- `RoleStrategy`
- `UserStrategy`

The controllers, taglib, and even the service never call strategy methods directly on the service, only via a strategy interface.

Each interface has a default implementation, e.g. `DefaultAcLStrategy`, `DefaultErrorsStrategy`, etc., and these simply delegate to `SpringSecurityUiService` (except for `MailStrategy`, which has `MailPluginMailStrategy` as its default implementation which uses the Mail plugin to send emails). Each of the default implementations is registered as a Spring bean:

- `uiAcLStrategy`
- `uiErrorsStrategy`
- `uiMailStrategy`
- `uiPersistentLoginStrategy`
- `uiPropertiesStrategy`
- `uiQueryStrategy`
- `uiRegistrationCodeStrategy`
- `uiRequestmapStrategy`
- `uiRoleStrategy`
- `uiUserStrategy`

To override the functionality defined in one of the strategy interfaces, register your own implementation of the interface in your application's `grails-app/conf/spring/resources.groovy`, e.g.

```
import com.myapp.MyRequestmapStrategy

beans = {
    uiRequestmapStrategy(MyRequestmapStrategy)
}
```

and yours will be used instead.

10.6. Password Verification

By default the registration controller has rather strict requirements for valid passwords; they must be between 8 and 64 characters and must include at least one uppercase letter, at least one number, and at least one symbol from “!@#\$\$%^&”. You can customize these rules with these

application.groovy attributes:

Property	Default Value
grails.plugin.springsecurity.ui.password.minLength	8
grails.plugin.springsecurity.ui.password.maxLength	64
grails.plugin.springsecurity.ui.password.validationRegex	"^.*(?=.*\d)(?=.*[a-zA-Z])(?=.*[!@#%&]).*\$"

Chapter 11. Scripts

11.1. s2ui-override

Purpose

Generates controllers that extend the plugin's controllers and copies their GSPs to your application for overriding of functionality.

The general format is:

```
grails s2ui-override <type> [controllerPackage]
```

The script will copy an empty controller that extends the corresponding plugin controller into your application so you can override individual actions and methods as needed. It also copies the controller's GSPs. The exceptions are when type is 'auth' or 'layout' which only copy GSPs.

See the [Customization](#) section for more details.